


R32 Multi-Splitsystemen

Binnenunits

Wandunit Performance

Binnenunit			RAK-15QPE	RAK-18RPE	RAK-25RPE	RAK-35RPE	RAK-42RPE	RAK-50RPE
Vermogen	Koelen (min./nom./max.)	kW	0,90-1,60-2,00	0,90-2,00-2,50	0,90-2,50-3,10	0,90-3,50-4,00	1,70-4,20-5,00	1,90-5,00-5,20
	Verwarmen (min./nom./max.)	kW	0,90-1,80-2,00	0,90-2,50-3,20	0,90-3,40-4,40	0,90-4,20-5,00	1,70-5,40-6,00	2,20-6,00-7,30
Luchtdebiet (zeer laag - laag - medium - hoog)	Koelen	m ³ /h	312-350-400-440	312-350-400-440	333-370-430-510	353-420-485-680	353-410-540-720	353-410-540-750
	Verwarmen	m ³ /h	312-350-420-480	312-350-420-480	333-400-500-570	363-480-570-780	380-500-610-800	380-500-610-820
Geluidsdrukkniveau (zeer laag - laag - medium - hoog)	Koelen	dB(A)	20-24-30-34	21-24-33-37	22-24-33-40	25-26-36-43	25-28-39-46	25-28-39-46
	Verwarmen	dB(A)	20-24-32-35	19-22-33-38	20-23-34-41	26-27-36-44	27-31-39-46	27-31-39-46
Geluidsvermogeniveau		dB(A)	47	51	54	57	60	60
Afmetingen (h x b x d)		mm	280 x 780 x 230	280 x 780 x 230	280 x 780 x 230	280 x 780 x 230	280 x 780 x 230	280 x 780 x 230
Gewicht		kg	8,5	8,5	8,5	8,5	8,5	8,5
Diameter leidingen	Vloeistof-gas	Inch	1/4-3/8	1/4-3/8	1/4-3/8	1/4-3/8	1/4-1/2	1/4-1/2
Diameter afvoer		mm	16	16	16	16	16	16
Voedingsspanning			1~230 V, 50 Hz	1~230 V, 50 Hz	1~230 V, 50 Hz	1~230 V, 50 Hz	1~230 V, 50 Hz	1~230 V, 50 Hz

Binnenunits



- RAK-18RPE
- RAK-25RPE
- RAK-35RPE
- RAK-42RPE
- RAK-50RPE



Accessoires voor room-airconditioners zijn combineerbaar met Multizone-units