


# R32 Multi-Splitsystemen

## Binnenunits

### Staande unit Shirokuma

Binnenunit			RAF-25RXE	RAF-35RXE	RAF-50RXE
Vermogen	Koelen (min./nom./max.)	kW	0,90-2,50-3,10	0,90-3,50-4,00	0,90-5,00-5,20
	Verwarmen (min./nom./max.)	kW	0,90-3,40-4,40	0,90-4,50-5,00	0,90-6,00-8,10
Luchtdebiet (zeer laag - laag - medium - hoog)	Koelen	m <sup>3</sup> /h	270-390-510-630	270-390-510-660	300-450-540-700
	Verwarmen	m <sup>3</sup> /h	300-420-540-660	300-420-540-660	330-480-570-730
Geluidsdrukniveau (zeer laag - laag - medium - hoog)	Koelen	dB(A)	20-26-31-38	20-26-31-38	22-29-36-42
	Verwarmen	dB(A)	20-26-31-38	20-26-31-38	22-29-36-43
Geluidsvermogeniveau		dB(A)	52	52	56
Afmetingen (h × b × d)		mm	750 × 590 × 215	750 × 590 × 215	750 × 590 × 215
Gewicht		kg	15,0	15,0	15,0
Diameter leidingen	Vloeistof-gas	Inch	1/4-3/8	1/4-3/8	1/4-1/2
Diameter afvoer		mm	16	16	16
Voedingsspanning			1~230 V, 50 Hz	1~230 V, 50 Hz	1~230 V, 50 Hz

#### Binnenunits



RAF-25RXE  
RAF-35RXE  
RAF-50RXE

