


R32 Multi-Splitsystemen

Binnenunits

Wandunit Shirokuma

Binnenunit			RAK-18QXE	RAK-25RXE	RAK-35RXE	RAK-50RXE
Vermogen	Koelen (min./nom./ max.)	kW	0,90-1,80-2,20	0,90-2,50-3,10	0,90-3,50-4,00	1,90-5,00-5,20
	Verwarmen (min./nom./ max.)	kW	0,90-2,50-3,10	0,90-3,20-4,20	0,90-4,00-4,80	2,20-5,80-7,00
Luchtdebiet (zeer laag - laag - medium - hoog)	Koelen	m ³ /h	300-330-510-600	300-330-510-600	320-340-520-660	350-400-580-720
	Verwarmen	m ³ /h	290-370-560-680	290-370-560-680	310-380-570-720	350-420-620-800
Geluidsdrukkniveau (zeer laag - laag - medium - hoog)	Koelen	dB(A)	20-25-30-36	20-27-35-43	22-29-37-45	25-31-39-47
	Verwarmen	dB(A)	20-26-32-38	20-28-36-43	22-30-37-45	25-31-39-48
Geluidsvermogeniveau		dB(A)	49	58	60	60
Afmetingen (h × b × d)		mm	295 × 900 × 210	295 × 900 × 210	295 × 900 × 210	295 × 900 × 210
Gewicht		kg	11	11	11	11
Diameter leidingen	Vloeistof-gas	Inch	1/4-3/8	1/4-3/8	1/4-3/8	1/4-1/2
Diameter afvoer		mm	16	16	16	16
Voedingsspanning			1~230 V, 50 Hz	1~230 V, 50 Hz	1~230 V, 50 Hz	1~230 V, 50 Hz

Binnenunits



RAK-25RXE
RAK-35RXE
RAK-50RXE

